



角接触轴承尺寸表 size of angular contact ball bearing

轴承型号 Bearing No.	外型尺寸 (mm) Boundary dimensions (mm)					相关安装尺寸 (mm) Mounting dimensions (mm)			重量 weight			轴承型号 Bearing No.
	d	D	B	r	r1	da	Da	ra	参考 refer (kg)			
						min	max	max	ZR02	SI3N4	POM	
7900CE	10	22	6	0.3	0.15	12.5	19.5	0.3	0.0070	0.0038	0.0010	P7900
7000CE		26	8	0.3	0.15	12.5	23.5	0.3	0.0140	0.0075	0.0030	P7000
7200CE		30	9	0.6	0.3	15	25	0.6	0.0250	0.0130	0.0040	P7200
7300CE		35	11	0.6	0.3	15	30	0.6	0.0400	0.0220	0.0070	P7300
7901CE	12	24	6	0.3	0.15	14.5	21.5	0.3	0.0080	0.0042	0.0010	P7901
7001CE		28	8	0.3	0.15	14.5	25.5	0.3	0.0170	0.0092	0.0030	P7001
7201CE		32	10	0.6	0.3	17	27	0.6	0.0280	0.0150	0.0050	P7201
7301CE		37	12	1	0.6	18	31	1	0.0460	0.0250	0.0080	P7301
7902CE	15	28	7	0.3	0.15	17.5	25.5	0.3	0.0120	0.0063	0.0020	P7902
7002CE		32	9	0.3	0.15	17.5	29.5	0.3	0.0240	0.0130	0.0040	P7002
7202CE		35	11	0.6	0.3	20	30	0.3	0.0350	0.0190	0.0060	P7202
7302CE		42	13	1	0.6	21	36	1	0.0640	0.0350	0.0110	P7302
7903CE	17	30	7	0.3	0.15	19.5	27.5	0.3	0.0130	0.0071	0.0020	P7903
7003CE		35	10	0.3	0.15	19.5	32.5	0.3	0.0320	0.0170	0.0060	P7003
7203CE		40	12	0.6	0.3	22	35	0.6	0.0520	0.0280	0.0090	P7203
7303CE		47	14	1	0.6	23	41	1	0.0870	0.0470	0.0160	P7303
7904CE	20	37	9	0.3	0.15	22.5	34.5	0.3	0.0280	0.0150	0.0050	P7904
7004CE		42	12	0.6	0.3	25	37	0.6	0.0520	0.0280	0.0090	P7004
7204CE		47	14	1	0.6	26	41	1	0.0820	0.0450	0.0150	P7204
7304CE		52	15	1.1	0.6	27	45	1	0.1100	0.0600	0.0200	P7304
7905CE	25	42	9	0.3	0.15	27.5	39.5	0.3	0.0320	0.0180	0.0060	P7905
7005CE		47	12	0.6	0.3	30	42	0.6	0.0610	0.0330	0.0110	P7005
7205CE		52	15	1	0.6	31	46	1	0.0990	0.0540	0.0180	P7205
7305CE		62	17	1.1	0.6	32	55	1	0.1800	0.0980	0.0320	P7305
7906CE	30	47	9	0.3	0.15	32.5	44.5	1	0.0400	0.0220	0.0070	P7906
7006CE		55	13	1	0.6	36	49	1	0.0890	0.0480	0.0160	P7006
7206CE		62	16	1	0.6	36	56	1	0.1500	0.0830	0.0270	P7206
7306CE		72	19	1.1	0.6	37	65	1	0.2700	0.1400	0.0480	P7306
7907CE	35	55	10	0.6	0.3	40	50	0.6	0.0580	0.0310	0.0100	P7907
7007CE		62	14	1	0.6	41	56	1	0.1200	0.0630	0.0220	P7007
7207CE		72	17	1.1	0.6	42	65	1	0.2200	0.1200	0.0390	P7207
7307CE		80	21	1.5	1	44	71	1.5	0.3600	0.1900	0.0650	P7307
7908CE	40	62	12	0.6	0.3	45	57	0.6	0.0900	0.0500	0.0160	P7908
7008CE		68	15	1	0.6	46	62	1	0.1500	0.0800	0.0270	P7008
7208CE		80	18	1.1	0.6	47	73	1	0.2800	0.1500	0.0500	P7208
7308CE		90	23	1.5	1	49	81	1.5	0.4900	0.2700	0.0880	P7308
7909CE	45	68	12	0.6	0.3	50	63	0.6	0.0970	0.0530	0.0170	P7909

轴承型号 Bearing No.	外型尺寸 (mm) Boundary dimensions (mm)					相关安装尺寸 (mm) Mounting dimensions (mm)			重量 weight			轴承型号 Bearing No.
	d	D	B	r	r1	da	Da	ra	参考 refer (kg)			
						min	max	max	ZR02	SI3N4	POM	
7009CE		75	16	1	0.6	51	69	1	0.1900	0.1000	0.0340	P7009
7209CE		85	19	1.1	0.6	52	78	1	0.3200	0.1750	0.0570	P7209
7309CE		100	25	1.5	1	54	91	1.5	0.6400	0.3450	0.1150	P7309
7910CE	50	72	12	0.6	0.3	55	67	0.6	0.1000	0.0600	0.0180	P7910
7010CE		80	16	1	0.6	56	74	1	0.2000	0.1100	0.0360	P7010
7210CE		90	20	1.1	0.6	57	83	1	0.3500	0.1900	0.0630	P7210
7310CE		110	27	2	1	60	100	2	0.8200	0.4400	0.1470	P7310
7911CE	55	80	13	1	0.6	61	74	1	0.1500	0.0800	0.0270	P7911
7011CE		90	18	1.1	0.6	62	83	1	0.2900	0.1600	0.0520	P7011
7211CE		100	21	1.5	1	64	91	1.5	0.4800	0.2600	0.0860	P7211
7311CE		120	29	2	1	65	110	2	1.0500	0.5700	0.1880	P7311
7912CE	60	85	13	1	0.6	66	79	1	0.1500	0.0800	0.0270	P7912
7012CE		95	18	1.1	0.6	67	88	1	0.3200	0.1700	0.0570	P7012
7212CE		110	22	1.5	1	69	101	1.5	0.6000	0.3300	0.1080	P7212
7312CE		130	31	2.1	1.1	72	118	2	1.3200	0.7200	0.2370	P7312
7913CE	65	90	13	1	0.6	71	84	1	0.1700	0.0900	0.0310	P7913
7013CE		100	18	1.1	0.6	72	93	1	0.3400	0.1800	0.0610	P7013
7213CE		120	23	1.5	1	74	111	1.5	0.7700	0.4200	0.1380	P7213
7313CE		140	33	2.1	1.1	77	128	2	1.6200	0.8800	0.2910	P7313
7914CE	70	100	16	1	0.6	76	94	1	0.2700	0.1500	0.0480	P7914
7014CE		110	20	1.1	0.6	77	103	1	0.4700	0.2500	0.0840	P7014
7214CE		125	24	1.5	1	79	116	1.5	0.8400	0.4500	0.1510	P7214
7314CE		150	35	2.1	1.1	82	138	2	1.9800	1.0700	0.3550	P7314
7915CE	75	105	16	1	0.6	81	99	1	0.2800	0.1500	0.0500	P7915
7015CE		115	20	1.1	0.6	82	108	1	0.5000	0.2700	0.0900	P7015
7215CE		130	25	1.5	1	84	121	1.5	0.9200	0.5000	0.1650	P7215
7916CE	80	110	16	1	0.6	86	104	1	0.3000	0.1600	0.0540	P7916
7016CE		125	22	1.1	0.6	87	118	1	0.6700	0.3600	0.1200	P7016
7216CE		140	26	2	1	90	130	2	1.0900	0.5900	0.1960	P7216
7917CE	85	120	18	1	1	91	109	1	0.3900	0.2080	0.0903	P7917
7017CE		130	22	1.1	0.6	92	123	1	0.7100	0.3800	0.1270	P7017
7217CE		150	28	2	1	95	140	2	1.3500	0.7300	0.2420	P7217
7918CE	90	125	18	1.1	0.6	97	118	1	0.4500	0.2400	0.0810	P7918
7018CE		140	24	1.5	1	99	131	1.5	0.9200	0.5000	0.1650	P7018
7218CE		160	30	2	1	100	150	2	1.7300	1.0100	0.4007	P7218
7919CE	95	130	18	1.1	0.6	102	123	1	0.4600	0.2500	0.0830	P7919
7019CE		145	24	1.5	1	104	136	1.5	0.9500	0.5100	0.1710	P7019
7219CE		170	32	2	1	105	160	2	2.0760	1.2123	0.4809	P7219
7920CE	100	140	20	1.1	0.6	107	133	1	0.6400	0.3500	0.1150	P7920
7020CE		150	24	1.5	1	109	141	1.5	0.9900	0.5400	0.1780	P7020
7220CE		180	34	2	1	110	170	1.5	2.4990	1.4590	0.5789	P7220
7921CE	105	145	20	1.1	0.6	112	138	1	0.6600	0.3600	0.1180	P7921
7021CE		160	26	1.5	1	114	146	1.5	1.2300	0.7184	0.2849	P7021
7221CE		190	36	2	1	115	180	1.5	2.9600	1.7287	0.6857	P7221
7922CE	110	150	20	1.1	0.6	117	143	1	0.6900	0.3700	0.1240	P7922
7022CE		170	28	1.5	1	119	151	1.5	1.4995	0.8756	0.3473	P7022
7222CE		200	38	2	1	120	190	1.5	3.4990	2.0430	0.8106	P7222